

TECHNICAL DATA SHEET

MULTIKLEEN 1922 - Acid Cleaner - Rust Remover

PAS-TDS-EPX-003

Description

MULTIKLEEN 1922 a blend of acids, inhibitors and solvents designed to prepare both cementitious and metal surfaces for over coating.

MULTIKLEEN 1922 contains acids and solvents. Wear protective clothing and gloves. In case of eye contact wash well with clean water and obtain medical assistance. Use in well ventilated areas.

Typical Applications

Preparation of metal reinforced floors, acid etching in sensitive environments, e.g. computer rooms, degreasing and de-rusting of steel surfaces and etching of galvanized surfaces.

Advantages

- Acts as a rust remover/ converter
Inhibits further rusting
- Improves
adhesion Low
toxicity
- Low acid vapour emission

Typical Properties

PH:	1-2
Appearance:	Clear
Application Rate:	2 - 10m ² / litre
Cleaning:	Water

Directions for Use

- Shake container well before use.
- For application to cementitious surfaces dilute 1 part of MULTIKLEEN 1922 with 3 parts of water.
- For application to metal surfaces, use as supplied.
- If used as a rust remover, first remove all loose scale and rust with a wire brush. Leave in contact for 10 minutes or until reaction has ceased. Rinse well with clean water. Repeat if necessary.

Watchpoints

- MULTIKLEEN 1922 contains acids and solvents.
- Wear protective clothing and gloves.
- In case of eye contact wash well with clean water and obtain medical assistance. Use in well ventilated areas.

Packaging

Supplied in 5 and 25 litre kits .

Updates: This data sheet supersedes all previous issues prior to this date: 31/05/97.